

AUTOMATIC TAPING MACHINE

COM[®] BBFII-200

BBFII is suitable for Paper tape and <F> is effective for Film tape operation

High performance taping (banding) machine featuring smallest, lightest and highest speed.




FEATURES

- Compact design with heavy duty operation
- Only 15 kg of easy portable design
- 24 cycles per minute is the highest speed
- Visible Heater temperature or Counter display is standard function

CAPABILITY

Model	Product size	Speed
BBF II -180	Max. (width 180mm, height 140mm) Min. (width 40mm, height 5mm)	24 cycles/minute
BBF II -200	Max. (width 200mm, height 140mm) Min. (width 40mm, height 5mm)	

Front Panel



MACHINE SPECIFICATIONS

Model	Tape width(mm)	Width	Height	Depth	height	Power supply	Tape
BBF II -180-20/30		320mm	380mm	210mm	240mm	115V/220V/230V 50Hz/60Hz	Paper tapes Film tapes
BBF II -180-40	215mm						
BBF II -200-20/30	210mm						
BBF II -200-40	215mm			Paper tapes			

COM TAPE SPECIFICATIONS

Type	Width	Thickness
Paper	20mm/30mm/40mm	70g (brown)/80g (white)
Film	20mm/30mm/40mm	100 micron

* Note: Use only the tapes supplied or approved by the machine manufacturer.

* Other than tapes mentioned above; color tapes, printed tapes, etc., can also be made to order.

* Specifications subject to change without notice.

COM is Communication



MUSASHI CO., LTD.

20-36, 8-chome, Ginza, Chuo-ku, Tokyo, Japan
 Phone / 81-3-3546-7820 Fax / 81-3-3546-7854
 URL / <https://www.musashinet.co.jp>
 E-mail / kaigai@musashinet.co.jp