

AUTOMATIC TAPING MACHINE

COM[®] JD II SERIES

Desk Top type for paper tape and film tape

Highly efficient, secure banding of a wide variety of works.

■ FEATURES

- Banding can be several times more efficient than that of hand taping.
- Patented mechanism for smooth tape feeding and taping.
- Heat adhesion system ensures very tight banding.
- Design features space saving and light weight for easy setting at any place.
- Digital temperature control system and counter system are efficient.

New Front Panel



CAPABILITY

Model	Product size	Speed
JD II -150F	Max. (width 150mm, height 140mm) Min. (width 30mm, height 5mm)	25 cycles/minute (approx.)
JD II -240	Max. (width 240mm, height 170mm) Min. (width 30mm, height 5mm)	

MACHINE SPECIFICATIONS

Model / Tape width (mm)	Width	Height	Depth	Table height	Power supply	Tape
JD II -150F-20 / 30	425mm	400mm	287mm	230mm	115V/220V/230V/240V 50Hz/60Hz	Film tapes
JD II -240-20 / 25 / 30			Paper tapes			
JD II -150F-40	435mm	400mm	300mm	230mm	115V/220V/230V/240V 50Hz/60Hz	Film tapes
JD II -240-40						Paper tapes

COM TAPE SPECIFICATIONS

Type	Width	Thickness
Paper	20mm/25mm/30mm/40mm	70g (brown)/80g (white)
Film	20mm/30mm/40mm	80 micron/100 micron/MAGIC CUT 110 micron

● Note: Use only the tapes supplied or approved by the machine manufacturer.

● Other than tapes mentioned above; color tapes, printed tapes, etc., can also be made to order.

● Specifications subject to change without notice.

COM is Communication

MUSASHI
MUSASHI CO., LTD.

20-36, 8-chome, Ginza, Chuo-ku, Tokyo, Japan
Phone: 81-3-3546-7820 Fax: 81-3-3546-7854
U R L : <https://www.musashinet.co.jp>
E-mail: kaigai@musashinet.co.jp